

VELCUT

Heat transfer flock-film > for plotter-cutting



VELCUT EVO

White 01		Lavender 29		Anis 35		Light Grey 19	
Lemon 02		Purple 30		Lime Green 23		Cool Grey 11	
Sunny Yellow 03		Dark Purple 31		Light Green 36		Dark Grey 39	
Orange 12		Mint 34		Green 10		Anthracite 18	
Electric Red 04		Sky Blue 15		Khaki 37		Black 06	
Red 05		Turquoise 20		Beige 16			
Dark red 26		Blue 32		Brown 22		Neon Yellow Premium	
Bordeaux 17		Pacific Blue 08		Chocolate 14		Neon Bright Orange Premium	
Pink 27		Royal Blue 09				Neon Orange Premium	
Magenta 21		Navy Blue 07				Neon Pink Premium	
Dark Pink 28						Neon Blue Premium	
						Neon Green Premium	

VELCUT TOUCH

White 91	
Lemon 92	
Yellow 93	
Orange 82	
Electric Red 94	
Red 95	
Pacific Blue 98	
Royal Blue 99	
Navy 97	
Light Grey 89	
Cool Grey 81	
Black 96	



Manufacturing processes and related products are protected by existing patents:

FR 97 12921; EUR 98 402 542.9; US 6.224.707; FR 98 12862; EUR 99 402 398.4; US 6.249.297; FR 04 08625; FR 05 05379; FR 05 05380;

international extensions and new applications pending.



VELCUT

Heat transfer flock-film > for plotter-cutting

Cut



VelCut Evo is a high quality flocked hot-melt film on polyester liner. It has good covering power and a high elasticity. For this reason, even subtle lines and scripts on plotters can be cut using a drag-knife or tangential cutting technology. Above all, **VelCut Evo** distinguishes itself from the rest with its excellent weeding characteristics.

VelCut Touch is the next generation flock film for plotter cutting. With VelCut Touch cutting and weeding intricate graphics is really easy! It cuts and weeds like a flex but VelCut Touch super soft feel surface is unique. **An innovative soft velour film that performs like a flex.**



VelCut Evo ist eine hochwertige beflockte Schmelzfolie auf Polyesterträger. Sie besitzt eine gute Deckkraft und hohe Elastizität. Es lassen sich damit selbst feinste Linien und Schriften auf Plottern mit Schleppmesser- oder Tangentialmessertechnik ausschneiden. **VelCut Evo** zeichnet sich vor allem aber durch seine hervorragenden Entgittereigenschaften aus.

VelCut Touch ist die nächste Generation Plotter fock. Selbst kleinste Motive werden mit VelCut Touch zum Kinderspiel. Schneiden und Entgittern ist genauso einfach wie bei FlexCut aber mit einer wundervoll weichen Oberfläche. **Eine „Flexfolie“ mit edelster Flockoberfläche!**



VelCut Evo est un film flocké de haute qualité sur un support en polyester. Il possède un grand pouvoir couvrant et une grande élasticité. Les lignes et les caractères les plus petits peuvent être découpés sur des plotters à lame oscillante ou tangentielle. Le **VelCut Evo** se caractérise avant tout par ses propriétés d'échenillage exceptionnelles.

VelCut Touch est un produit unique et très innovant qui va réconcilier les utilisateurs de flex et de flock. **La finesse et la facilité de découpe d'un flex avec un touché microfibre d'une douceur incroyable !**




1



Scan or create a digital vector image.

2



Cut a mirror-image of your design on a plotter-cutting machine.

3



Apply with an electric press

COMPOSITION

Base	Hotmelt film
Adhesive	Synthetic Resin
Flock	VelCut Evo, Standard colors : Rayon viscosé VelCut Evo, Neon colors : Polyamid VelCut Touch : Micro viscosé
Thickness	VelCut Evo : 500 µ VelCut Touch : 300 µ

TECHNICAL INFO

Washing fastness	up to 60°C (140°F)
Transfer	15 - 17 seconds / 160 - 170°C (320 - 340°F) Low / medium pressure

APPLICATION

	PACKAGING	
	50 cm (19")	30 meters (32,7 yd)
Cotton	50 cm (19")	25 meters (27,3 yd)
Poly/Cotton	50 cm (19")	10 meters (10,9 yd)
Polyester	50 cm (19")	5 meters (5,4 yd)



110 Bd Denis-Papin - 53000 LAVAL - France
Tél : 33 (0) 2 43 53 36 48
Fax : 33 (0) 2 43 67 11 78
Email : contact@sef-france.com
www.seftextile.com



SEF AMERICAS
14476 Duval Place West / Ste.201
Jacksonville, FL32218 / 904-423-0211 - Phone / USA
sales@SEFamericas.com
www.sefamericas.com